

## IS 168

## 产品简介

名称：脂肪醇聚氧烷基化合物（高效脱脂剂）

产品类型：非离子型表面活性剂

**产品说明及特性：** 该产品具有优异的润湿、乳化性能，主要应用于皮革工业，用作浸水助剂、脱脂剂、润湿剂等，适用于所有原料皮的浸水与脱脂。同时也可广泛应用于纺织（主要应用于前处理剂、硅油乳化剂）、洗涤、清洁及其它化工行业。因其非离子特性，可与阴离子，阳离子及其它非离子表面活性剂和助剂等共同使用；

## 技术指标

项目 / 单位	典型值	测试标准
外观 (25°C)	无色液体	-
色泽 Pt-Co	≤30	GB/T 9282.1-2008
水分 /%(m/m)	≤0.3	GB/T 6283-2008
pH (1% 水溶液)	5.0-7.0	GB/T 6368-2008
浊点 /°C	约 67	GB/T 5559-2010: 5g 表活 +45g 25% 的 二乙二醇丁醚水溶液
粘度 /mPas (23°C)	约 60	-
HLB	约 12.5	水数法

## 应用性能

项目 / 单位	典型值	测试标准
表面张力 /mN/m	27.15	1g/L 水溶液
动态表面张力 / mN/m (0.1s)	40.6	1g/L 水溶液
泡沫高度 /mm	135	1g/L 水溶液， 流量 0.3L/min，30°C
润湿性能 /s	46	GB/T 11983-2008

产品包装及贮运要求 

本产品采用 190kg 桶包装； 产品无毒，不易燃，按一般化学品贮存和运输； 贮存于干燥通风处，保质期 2 年。

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer' s use and for ensuring that Customer' s workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.